



Village of Arlington Heights
Building & Life Safety Department
847-368-5560
www.vah.com

Sewer Repair-Clean Out Street Opening Acknowledgment

November 1 to May 1. Winter Conditions. No Plates Allowed In Street.

Temporary Patch Requirements (Cold Patch)

- ❖ Backfill with CA-6 In 6" compacted lifts.
- ❖ Cap off with 2" of compacted cold patch.
- ❖ Contractor to maintain patch on a weekly basis until permanent patch can be placed.

Permanent Patch Requirements (Hot Patch) The minimum patch consists of the following:

- ❖ 6" of compacted Hot Mix Asphalt (HMA) Binder Course (2" Lifts)
- ❖ 2" of compacted surface course.
- ❖ For existing pavements greater than 8" thick, increase Asphalt Binder thickness accordingly.

It shall be the Plumber and/or Sewer & Water contractor's responsibility to coordinate the repair and/or patching of public street.

Paving contractor shall be licensed with the Village of Arlington Heights. A refundable bond of \$500 is due at time of permit application.

Bond shall be retained for 1 year after hot patch to ensure integrity of patch.

Pre-pour inspection is required prior to hot patch placement.
Final inspection shall be performed by the Engineering Division of the Public Works Department one year after hot patch has been completed.

Emergency repair work shall apply for permit the next business day.

The undersigned has read and understands the information provided in this informational handout, and agrees to comply with all applicable Village codes.

Date: _____ **Signature:** _____ **Print Name:** _____

Job-Site Address: _____

E-mail Address: _____

Company Name: _____ **Company Phone:** _____

Company Address: _____

City: _____ **State:** _____ **Zip:** _____