



**VILLAGE OF ARLINGTON HEIGHTS**  
DEPARTMENT OF BUILDING & HEALTH SERVICES  
33 S. Arlington Heights Rd.  
Arlington Heights, IL 60005  
Phone (847) 368-5560  
Fax (847) 368-5975  
Website: www.vah.com

**SEWER REPAIR-CLEAN OUT**  
**STREET OPENING ACKNOWLEDGEMENT**

**November 1 to May 1. Winter Conditions. No Plates Allowed In Street.**

**Temporary Patch Requirements** (Cold Patch)

- ◆ Backfill with CA-6 In 6" compacted lifts.
- ◆ Cap off with 2" of compacted cold patch.
- ◆ Contractor to maintain patch on a weekly basis until permanent patch can be placed.

**Permanent Patch Requirements** (Hot Patch)

The minimum patch consists of the following:

- ◆ 6" of compacted Bituminous Aggregate Material (B.A.M.) (2" Lifts)
- ◆ 2" of compacted surface course.
- ◆ For existing pavements greater than 8" thick, increase Bituminous Aggregate Material (B.A.M.) thickness accordingly.

It shall be the Plumber and/or Sewer & Water contractor's responsibility to coordinate the repair and/or patching of public street.

Paving contractor shall be licensed with the Village of Arlington Heights.

A refundable bond of \$200 is due at time of application.

**Bond shall be retained for 1 year after hot patch to ensure integrity of patch.**

Pre-pour inspection is required prior to hot patch placement.

Final inspection shall be performed by the Engineering Department and Public Works Street Department one year after hot patch has been completed.

Emergency repair work shall apply for permit the next business day.

The undersigned has read and understands the information provided in this informational handout, and agrees to comply with all applicable Village codes.

**Date:** \_\_\_\_\_ **Signature:** \_\_\_\_\_ **Print Name:** \_\_\_\_\_

**Job-Site Address:** \_\_\_\_\_

**E-Mail Address:** \_\_\_\_\_

**Company Name:** \_\_\_\_\_ **Company Phone:** \_\_\_\_\_

**Company Address:** \_\_\_\_\_

**City:** \_\_\_\_\_ **State:** \_\_\_\_\_ **Zip Code:** \_\_\_\_\_