

New Construction Energy Code Compliance Certificate

Per R4013 Certificate. A building certificate shall be posted on or in the electrical distribution panel.

Date Certificate Posted



Mailing Address of the Dwelling or Dwelling Unit

City

Name of Residential Contractor

MN License Number

THERMAL ENVELOPE

RADON CONTROL SYSTEM

Insulation Location	Total R-Value of all Types of Insulation	Type: Check All That Apply								Other Please Describe Here
		Non or Not Applicable	Fiberglass, Blown	Fiberglass, Batts	Foam, Closed Cell	Foam Open Cell	Mineral Fiberboard	Rigid, Extruded Polystyrene	Rigid, Isocynurate	
Below Entire Slab										Passive (No Fan) Active (With fan and monometer or other system monitoring device) Location (or future location) of Fan:
Foundation Wall										
Perimeter of Slab on Grade										
Rim Joist (1st Floor)										
Rim Joist (2nd Floor+)										
Wall										
Ceiling, flat										
Ceiling, vaulted										
Bay Windows or cantilevered areas										
Floors over unconditioned area										
Describe other insulated areas										

Building envelope air tightness: _____ Duct system air tightness: _____

Windows & Doors	Heating or Cooling Ducts Outside Conditioned Spaces
Average U-Factor (excludes skylights and one door)	Not applicable, all ducts located in conditioned space
Solar Heat Gain Coefficient (SHGC):	R-value

MECHANICAL SYSTEMS

MECHANICAL SYSTEMS				Make-up Air <i>Select a Type</i>	
Appliances	Heating System	Domestic Water Heater	Cooling System	Not required per mech. code	
Fuel Type				Passive	
Manufacturer				Powered	
Model				Interlocked with exhaust device.	
Rating or Size	Input in BTUS:	Capacity in Gallons:	Output in Tons:	Other, describe:	
Efficiency	AFUE or HSPF%		SEER /EER	Location of duct or system:	
Residential Load Calculation	Heating Loss	Heating Gain	Cooling Load		
				Cfm's	
				" round duct OR	
				" metal duct	

MECHANICAL VENTILATION SYSTEM

Describe any additional or combined heating or cooling systems if installed: (e.g. two furnaces or air source heat pump with gas back-up furnace):				Combustion Air <i>Select a Type</i>	
				Not required per mech. code	
Select Type				Passive	
Heat Recover Ventilator (HRV) Capacity in cfm's:	Low:	High:		Other, describe:	
Energy Recover Ventilator (ERV) Capacity in cfm's:	Low:	High:		Location of duct or system:	
Balanced Ventilation capacity in cfm's:					
Location of fan(s), describe:				Cfm's	
Capacity continuous ventilation rate in cfm's:				" round duct OR	
Total ventilation (intermittent + continuous) rate in cfm's:				" metal duct	